BRAND:	FONDITAL

MODEL:	eBLITZ Wi-Fi

LAST UPDATED:	12/01/21

STANDARDS	SEASONAL SPACE HEATING ENERGY EFFICIENCY
CE, ERP-Ecodesign Compliance	ηs = 40 %

PRODUCT PICTURES

Included Accessories

Fixing brackets (H system), blocks and screws.

TECHNICAL DESCRIPTION	
MATERIAL	Aluminum
FLUDIE TYPE	Mineral oil
COLOR	White RAL9010
HEATING ELEMENT	Constant power, safety thermostat, thermal fuse
THERMOSTAT	Electronic, backlighted
WALL FIXATION	Included
IP GRADE	IP24
ELECTRIC INSULATION	CLASS II

FUNCTIONS	
ON / OFF SWITCH	Yes
DISTANCE CONTROL	Yes (WI-Fi + APP)
PROGRAMMING CONTROL	Weekly and daily
CLOCK BACK-UP	> 2 h
PILOT WIRE 6 ORDERS	Yes
SMART FUNCTIONS	Window opening function Consumption metering Adaptive control of start-up
OTHER FUNCTIONS	Menu-driven user interface

Model	Output	Thickness	Height	Lenght	Net weight	Nr. of elements
eBlitz Wi-Fi	W	mm	mm	mm	Kg	
750 W	750	80	583	390	8	4
1000 W	1000	80	583	470	9,9	5
1250 W	1250	80	583	630	13,7	7
1500 W	1500	80	583	790	17,1	9
1800 W	1800	80	583	950	19,7	11

STICKERS

CABLE		
110 cm lenght	L + N + Pilot Wire	

INSTRUCTION BOOK		
IST 03 F 106 -01 A4 FORMAT		
Italian	German	English
IST 03 F 108 -01 A4 FORMAT		
French	Spanish	Portuguese

PACKAGING PICTURES



WI-FI REMOTE CONTROL

APP **"Domus One"**



DISPONIBLE SUR Google Play

Wi-Fi 2,54 GHz, with the following network protection methods:

- WPA-PSK
- WPA2-PSK
- open network (no security implemented).

Not supported any other method, such as WEP (system that still use WEP aren't secure).
Wi-Fi SSID network names and passwords cannot exceed 50 characters.